

Hot water high-pressure washers from CLENA are the epitome of washing performance. With water temperatures of 100°C and more, they remove every kind of residue in demanding industrial cleaning applications. Powerful combinations of water and pressure enable a wide range of applications.



INCLUDED



Standard accessory kit SWS:

- 10 m high-pressure hose DN10, kink protection on both sides
- High-pressure gun HDP350 with quick coupling and swivel joint in the inlet
- Double jet pipe made of stainless steel with high- and low-pressure nozzle

EQUIPMENT

- Epoxy-coated steel frame with stainless steel cover
- Four-wheel chassis with rubber tyres
- Powerful motors in many performance classes with long service life due to low speed (1.450/1750 1/min)
- Triplex high-pressure pump with brass cylinder head, full ceramic pistons and stainless steel valves, oil-bath lubricated, low-noise and vibration-free
- Automatic pressure relief of the high-pressure hose
- Water inlet temperature up to 60 °C
- Heating capacity 90 kW
- Water outlet temperature up to 100 °C
- Automatic start-stop (optionally pressure or flow controlled, please specify when ordering)
- Diesel tank capacity approx. 32 L

MODEL VARIATIONS

Art.No.	Pressure bar	Flow rate L/min	Power kW	Nozzle	Power supply	Dimensions L mm x W mm x H mm	Weight kg approx.
M2014040	160	14	4.0	045	400 V, 3 phases, 50/60 Hz	1070 x 620 x 870	125 to 170
M2015040	150	15	4.0	055			
M2015055	200	15	5.5	045	400 V, 3 phases, 50/60 Hz	1070 x 620 x 870	125 to 170
M2018055	170	18	5.5	060			
M2021055	150	21	5.5	075			
M2015065	240	15	6.5	045	400 V, 3 phases, 50/60 Hz	1070 x 620 x 870	125 to 170
M2018065	200	18	6.5	055			
M2021065	170	21	6.5	070			
M2025065	150	25	6.5	090			
M2021075	200	21	7.5	065	400 V, 3 phases, 50/60 Hz	1070 x 620 x 870	125 to 170
M2025075	170	25	7.5	080			
M2030075	150	30	7.5	100			

EQUIPMENT OPTIONS (ONLY IN CONNECTION WITH UNIT ORDER)

Option	Art.No.
Flame monitoring optical	CLAO0100
Chimney transition piece Rectangular 400mm	CLAO0101
ASR20 equipment Equipment mounting bracket, automatic hose reel galvanised, 20m high-pressure hose, quick-change system	CLAO0160
Attachment kit water inlet filter 5" With sand filter insert	CLAO0071