

The entry-level model for the discerning customer, combining robust performance with a highly competitive price. Ideal for a wide range of general cleaning applications.



INCLUDED



Standard accessory kit SWS:

- 10 m high pressure hose DN10, kink protection on both sides
- High-pressure gun HDP350 with quick coupling und swivel joint on the inlet
- Double jet pipe made of stainless steel with high- and low-pressure nozzle

EQUIPMENT

- Epoxy-coated steel frame with plastic cladding
- Four-wheel chassis with rubber tyres
- Powerful engines in several performance classes with long service life due to low speed (1.450 1/min)
- Triplex high pressure pump with brass cylinder head, full ceramic pistons and stainless steel valves, oil-bath lubricated, low-noise and vibration-free
- Automatic start-stop (timer-controlled and flow-controlled)
- Automatic pressure relief of the high pressure hose
- Water inlet temperature up to 60 °C
- Heating capacity approx. 65 kW
- Water outlet temperature up to 100 °C
- Diesel tank capacity approx. 20 L

SERIES MC2000**MODEL VARIATIONS**

| Art.No. | Pressure bar | Flow rate L/min | Power kW | Nozzle | Power supply | Dimensions L mm x W mm x H mm | Weight kg approx. |
|-----------|-----------------|--------------------|-------------|--------|------------------------|----------------------------------|----------------------|
| MC2011022 | 120 | 11 | 2.2 | 035 | 230 V, 1 phase | 1070 x 620 x 870 | 110 |
| MC2014040 | 160 | 14 | 4.0 | 045 | 400 V, 3 phases, 50 Hz | 1070 x 620 x 870 | 110 |
| MC2018055 | 170 | 18 | 5.5 | 060 | 400 V, 3 phases, 50 Hz | 1070 x 620 x 870 | 110 |
| MC2021055 | 150 | 21 | 5.5 | 075 | | | |