

If no change of location is planned, our stationary high- and low-pressure systems offer you the greatest cleaning possibilities in the smallest space. Available with a variety of options such as floor stand, descaling unit, chemical injection and much more.



Version with optionally available floor stand

INCLUDED



Standard accessory kit SWS:

- 10 m high-pressure hose DN10, kink protection on both sides
- High-pressure gun HDP350 with quick coupling and swivel joint in the inlet
- Double jet pipe made of stainless steel with high- and low-pressure nozzle

EQUIPMENT

- Epoxy-coated steel frame with stainless steel cover
- Powerful motors in many performance classes with long service life due to low speed (1.450/1750 1/min)
- Triplex high-pressure pump with brass cylinder head, full ceramic pistons and stainless steel valves, oil-bath lubricated, low-noise and vibration-free
- Automatic pressure relief of the high-pressure hose
- With flame monitoring
- Water inlet temperature up to 60 °C
- Heating capacity 90 kW
- Water outlet temperature up to 100 °C
- Automatic start-stop (optionally pressure or flow controlled, please specify with order)
- External fuel oil suction (no fuel oil tank)

MODEL VARIATIONS

Art.No.	Pressure bar	Flow rate L/min	Motor power kW	Nozzle	Power supply	Dimensions L mm x W mm x H mm	Weight kg approx.
ST2015040	150	15	4.0	055	400 V, 3 phases, 50/60 Hz	1.280 x 580 x 750	105 to 190
ST2015055	200	15	5.5	045	400 V, 3 phases, 50/60 Hz	1.280 x 580 x 750	105 to 190
ST2018055	170	18	5.5	060			
ST2021055	150	21	5.5	075			
ST2015065	240	15	6.5	045	400 V, 3 phases, 50/60 Hz	1.280 x 580 x 750	105 to 190
ST2018065	200	18	6.5	055			
ST2021065	170	21	6.5	070			
ST2025065	150	25	6.5	090			
ST2021075	200	21	7.5	065	400 V, 3 phases, 50/60 Hz	1.280 x 580 x 750	105 to 190
ST2025075	170	25	7.5	080			
ST2030075	150	30	7.5	100			

EQUIPMENT OPTIONS (ONLY IN CONNECTION WITH UNIT ORDER)

Option	Art.No.
Chimney transition piece Rectangular 400 mm	CLAO0101
Floor rack Epoxy-coated steel Stainless steel	CLAO0054 CLAO0055
Hot water pump kit For water inlet temperatures up to 80 °C	CLAO0090
Operating hours counter 380 V In separate control box IP66 with connection cable 1,0 m	CLAO0110
Stainless steel frame	On request
Built-in descaling with tank	On request