

The ideal solution for permanently installed cleaning appliances that can be connected to hose reels or pipelines, as stand-alone units or as an integrated cleaning system. The greatest cleaning possibilities in the smallest space!



Version with optionally available floor rack

INCLUDED



Standard accessory kit SWS:

- 10 m high-pressure hose DN10, kink protection on both sides
- High-pressure gun HDP350 with quick coupling and swivel joint in the inlet
- Double jet pipe made of stainless steel with high- and low-pressure nozzle

EQUIPMENT

- Epoxy-coated steel frame with noise and vibration damped stainless steel cover
- Powerful motors in many performance classes with long service life due to low speed (1.450/1750 1/min)
- Triplex high-pressure pump with brass cylinder head, full ceramic pistons and stainless steel valves, oil-bath lubricated, low-noise and vibration-free
- Vibration-damping rubber feet
- Control cabinet made of powder-coated steel (IP66)
- Function switch 1-0-2 with indicator light stand-by
- Automatic start-stop (optionally pressure or flow controlled, please specify when ordering)
- 24 V control
- Restart monitoring
- Externally routed earthing
- Water inlet temperature up to 60 °C

MODEL VARIATIONS

Art.No.	Pressure bar	Flow rate L/min	Power kW	Nozzle	Power supply	Dimensions L mm x W mm x H mm	Weight kg approx.
ST2515040	150	15	4.0	055	400 V, 3 phases, 50/60 Hz	685 x 425 x 685	95
ST2515055	200	15	5.5	045	400 V, 3 phases, 50/60 Hz	685 x 425 x 685	95
ST2518055	170	18	5.5	060			
ST2521055	150	21	5.5	075			
ST2515065	240	15	6.5	040	400 V, 3 phases, 50/60 Hz	685 x 425 x 685	95
ST2518065	200	18	6.5	055			
ST2521065	170	21	6.5	070			
ST2525065	150	25	6.5	090			
ST2521075	200	21	7.5	065	400 V, 3 phases, 50/60 Hz	685 x 425 x 685	95
ST2525075	170	25	7.5	080			
ST2530075	150	30	7.5	100			

EQUIPMENT OPTIONS (ONLY IN CONNECTION WITH UNIT ORDER)

Option	Art.No.
Floor rack	
Black, Epoxy-coated	CLAO0052
Stainless steel	CLAO0053
Frame in stainless steel	
(Instead of Epoxy-coated)	CLAO0044
Wall suspension	
Black, Epoxy-coated	CLAO0180
Stainless steel	CLAO0181
Hot water pump kit	
For water inlet temperatures up to 80 °C	CLAO0090
Temperature monitoring	
With indicator light and switch-off if temperature is too high	CLAO0211
Pre-pressure monitoring	
With indicator light and switch-off if pressure is too low (P less than 2 bar)	CLAO0221
Operating hours counter	
Inside the control box	CLAO0232
Running time control	
Standby / total stop	CLAO0600
Time-of-day release	
Standby / total stop	CLAO0700
Integrated float box	
7 L, for units up to 21 L/min	CLAO0800
Remote control	
With 10 m control cable (with emergency stop switch, function switch 1-0-2 and indicator light stand-by)	CLAO0270
Water filter	
With wall bracket	CLAO0073