

**WEEDEX hot water devices use the most efficient method for chemical-free weed control!** The hot water penetrates the soil layer and destroys the cell structure of the plant. Due to this root-deep effect, a low treatment frequency is achieved, as well as a high area performance. In addition, the **flow heater can also be used as a HotBox for high-pressure applications** up to 200 bar!



**INCLUDED**



- Hand sprayer trolley made of stainless steel for surface treatment:
- 1100 mm long handle tube
  - 400 mm working width and 4 nozzles for concentrated hot water energy
  - Sturdy industrial rollers for all surfaces

**EQUIPMENT**

- Epoxy-coated steel frame with stainless steel cover
- Four-wheel chassis with rubber-tyres
- Heating capacity approx. 90 kW
- Water outlet temperature 85-100°C
- Connection hose 1,5 m
- Flame monitoring (optical)
- Thermal switch and flow monitoring
- Diesel fuel tank capacity approx. 16 L

**MODEL VARIATIONS**

Art.No.	Pressure bar	Flow rate L/min	Power supply	Fuel tank L Diesel	Dimensions L mm x W mm x H mm	Weight kg approx.
MWE200	6-8 max. 200 bar	8-14 with high-pressure application up to 28	230 V, 1 phase	16	700 x 570 x 800	65
MWE300	6-8 max. 300 bar	8-14 with high-pressure application up to	230 V, 1 phase	16	700 x 570 x 800	65

**EQUIPMENT OPTIONS**

Option	Art.No.
<b>Single lance with weed control attachment</b>	CLAO1000