

If no change in location is planned, our stationary high- and low-pressure systems offer you the greatest cleaning possibilities in the smallest space. This is the most cost-saving stationary solution when no cover is required, e.g. in stables and milking parlours.



INCLUDED



Standard accessory kit SWS:

- 10 m high-pressure hose DN10, kink protection on both sides
- High-pressure gun HDP350 with quick coupling and swivel joint in the inlet
- Double jet pipe made of stainless steel with high- and low-pressure nozzle

EQUIPMENT

- Powerful motors in many performance classes with long service life due to low speed (1.450/1750 1/min)
- Triplex high-pressure pump with brass cylinder head, full ceramic pistons and stainless steel valves, oil-bath lubricated, low-noise and vibration-free
- Water inlet temperature up to 60 °C
- Direct start by contactor control with motor protection switch
- Automatic start-stop with flow switch
- Connection cable 10.0 m with 16 A plug
- Preparation for wall mounting

MODEL VARIATIONS

Art.No.	Pressure bar	Flow rate L/min	Power kW	Nozzle	Power supply	Dimensions L mm x W mm x H mm
STC251505	200	15	5.5	045	400 V, 3 phases, 50/60 Hz	630 x 370 x 455
STC251805	170	18	5.5	060		
STC252105	150	21	5.5	075		
STC251506	240	15	6.5	045	400 V, 3 phases, 50/60 Hz	630 x 370 x 455
STC251806	200	18	6.5	055		
STC252106	170	21	6.5	070		
STC252506	150	25	6.5	090		

EQUIPMENT OPTIONS (ONLY IN CONNECTION WITH UNIT ORDER)

Option	Art.No.
Hot water pump kit For water inlet temperatures up to 80 °C	CLAO0090
Remote control With 10 m control cable (with emergency stop switch, function switch 1-0-2 and indicator light stand-by)	CLAO0270
Wall rack Stainless steel	CLAO0060