

The ideal solution for permanently installed cleaning appliances that can be connected to hose reels or pipelines, as stand-alone units or as an integrated cleaning system. The greatest cleaning possibilities in the smallest space!



INCLUDED



Standard accessory kit SWS:

- 10 m high-pressure hose DN10, kink protection on both sides
- High-pressure gun HDP350 with quick coupling and swivel joint in the inlet
- Double jet pipe made of stainless steel with high- and low-pressure nozzle

EQUIPMENT

- Epoxy-coated steel frame with noise and vibration damped stainless steel cover
- Powerful motors in many performance classes with long service life due to low speed (1.450/1750 1/min)
- Triplex high-pressure pump with brass cylinder head, full ceramic pistons and stainless steel valves, oil-bath lubricated, low noise and vibration-free
- Automatic start-stop (optionally pressure or flow controlled, please specify when ordering)
- Water inlet temperature up to 60 °C

Art.No.	Pressure bar	Flow rate L/min	Power kW	Nozzle	Power supply	Dimensions L mm x W mm x H mm	Weight kg approx.
ST151505 5	200	15	5.5	045	400 V, 3 phases, 50/60 Hz	685 x 410 x 355	70
ST151805 5	170	18	5.5	060			
ST152105 5	150	21	5.5	075			
ST151506 5	240	15	6.5	040	400 V, 3 phases, 50/60 Hz	685 x 410 x 355	70
ST151806 5	200	18	6.5	055			
ST152106 5	170	21	6.5	070			
ST152506 5	150	25	6.5	090			
ST152107 5	200	21	7.5	065	400 V, 3 phases, 50/60 Hz	685 x 410 x 355	70
ST152507 5	170	25	7.5	080			
ST153007 5	150	30	7.5	100			

EQUIPMENT OPTIONS (ONLY IN CONNECTION WITH UNIT ORDER)

Option	Art.No.
Floor rack Black, Epoxy-coated Stainless steel	CLAO0052 CLAO0053
Frame in stainless steel (Instead of Epoxy-coated)	CLAO0044
Wall suspension Black, Epoxy-coated Stainless steel	CLAO0180 CLAO0181
Hot water pump kit For water inlet temperatures up to 80 °C	CLAO0090
Remote control With 10 m control cable (with emergency stop switch, function switch 1-0-2 and indicator light stand-by)	CLAO0274
Water filter With wall bracket	CLAO0073